

Clamp with Worm-Gear Drive 304 Stainless Steel

Stainless steel worm-gear-drive hose clamp in W4 / 304 stainless steel (1.4301), for securing light and medium-duty flexible hoses and ducting where corrosion resistance is needed. Even, adjustable clamping pressure via the worm-drive screw.

Stainless steel

Screwable

Corrosion-protected



CONSTRUCTION & MATERIALS

- Clamp Design: clamp band designed with a band width of approx. 12 mm
- clamp band designed with a
- Material of the clamp: stainless steel 1.4301
- material grade W5

PROPERTIES

- Chemical Properties: rust-protected

VARIANT SPECIFICATIONS

34 sizes · 40-600 mm

Order code	Clamp size (mm)	Clamping range (mm)
620SS-040-060	40	40-60
620SS-050-070	50	50-70
620SS-060-080	60	60-80
620SS-070-090	70	70-90
620SS-080-100	80	80-100
620SS-090-110	90	90-110
620SS-100-120	100	100-120
620SS-110-130	110	110-130
620SS-120-140	120	120-140
620SS-130-150	130	130-150
620SS-140-160	140	140-160
620SS-150-170	150	150-170
620SS-160-180	160	160-180
620SS-170-190	170	170-190
620SS-180-200	180	180-200
620SS-190-210	190	190-210
620SS-200-220	200	200-220
620SS-210-230	210	210-230
620SS-220-240	220	220-240
620SS-240-260	240	240-260
620SS-250-270	250	250-270
620SS-270-290	270	270-290
620SS-280-300	280	280-300
620SS-290-310	290	290-310
620SS-300-320	300	300-320
620SS-310-330	310	310-330
620SS-330-350	330	330-350
620SS-340-360	340	340-360
620SS-360-380	360	360-380
620SS-400-420	400	400-420
620SS-410-430	410	410-430
620SS-460-480	460	460-480
620SS-510-530	510	510-530
620SS-600-620	600	600-620

Order using the code shown. Made to order – see flex-appeal.co.uk for current stock and lead times.