

FLAMEX B-F BLACK

Ref 000388

Black Light/Medium duty Polyurethane Abrasion Resistant Ducting Hose, PU,
Copper coated steel



Compressible

Very flexible

Moderately pressure resistant

-40 to +90 °C

CONSTRUCTION & MATERIALS

- Construction: film hose with metal spiral
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Wall: made of highly abrasion-resistant material / made of pure material / wall thickness between the spirals approx. 0.5 mm
- Wall material: polyester polyurethane

PROPERTIES

- Chemical resistance: good resistance to oil
- Flexibility: very flexible
- Pressure: moderately pressure resistant

TEMPERATURE

- Operating range: 40 to 90 °C
- Short-term peak: peaks to 125 °C

VARIANT SPECIFICATIONS

6 sizes · DN 75 to 200 mm

Article no.	DN (mm)	Outer Ø (mm)	Bend radius (mm)	Weight (kg/m)	Working press. (bar)	Vacuum (bar)
000388:75:x	75	83	43	0.52	0.61	0.13
000388:100:x	100	108	55	0.69	0.46	0.09
000388:125:x	125	136	68	0.85	0.38	0.09
000388:150:x	150	159	80	1.02	0.30	0.09
000388:160:x	160	169	85	1.08	0.30	0.06
000388:200:x	200	210	105	1.26	0.23	0.06

Lengths. Supplied in standard stock lengths – see flex-appeal.co.uk for available sizes.