

Hose Connector

A galvanised sheet-steel sleeve connector used to join, extend or couple two lengths of light to medium-weight flexible hose or ducting. Slides inside the hose ends and is secured with a clamp at each side.

Galvanised steel



CONSTRUCTION & MATERIALS

- Design of the hose connector: round-rolled sheet steel with central, outwardly directed reinforcing beads
- Material of the hose connector: sheet steel, galvanised

PROPERTIES

- Chemical Properties: rust-protected
- Other: easy to assemble

VARIANT SPECIFICATIONS

23 sizes · 50–450 mm

Order code	Hose Ø DN (mm)	Insertion depth (mm)	Length (mm)
630-050-0000	50	36	78
630-060-0000	60	36	78
630-065-0000	65	36	78
630-075-0000	75	36	78
630-080-0000	80	36	78
630-090-0000	90	36	78
630-100-0000	100	36	78
630-110-0000	110	36	78
630-120-0000	120	36	78
630-125-0000	125	36	78
630-130-0000	130	36	78
630-140-0000	140	36	78
630-150-0000	150	36	78
630-160-0000	160	36	78
630-180-0000	180	36	78
630-200-0000	200	36	78
630-225-0000	225	36	78
630-250-0000	250	36	78
630-300-0000	300	36	78
630-315-0000	315	36	78
630-350-0000	350	36	78
630-400-0000	400	36	78
630-450-0000	450	36	78

Order using the code shown. Made to order — see flex-appeal.co.uk for current stock and lead times.